



FEATURES

A small profile LED track light that delivers optimal lumen output, with precise aiming for accent, task, or general illumination, integrating into any design. Track heads are adjustable up to 360 degrees horizontally, 180 degrees vertically, and are compatible with 1-circuit and 2-circuit track. With the use of a friction-based locking movement system, the head can be adjusted and re-adjusted to a precise position, delivering light where needed. Available in an array of color temperatures, it can accentuate the full spectrum of cool to warm tones, and is the perfect complement for retail merchandising, galleries, museums, supermarkets, hospitality, and commercial.

OPTICS



SP Spot 15°	NFL Narrow Flood 24°, 25°	FL Flood 36°, 38°	WFL Wide Flood 60°
--------------------------	--	--------------------------------	---------------------------------

NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
600	635	10 W

Based on 3000K, 90+ CRI. Actual wattage may vary +/- 5%

LUMENS	600
CCT	30K
CRI	90+
COLOR QUALITY	2 Step MacAdam Ellipse
DISTRIBUTION	SP (Spot), NFL (Narrow Flood), FL (Flood), WFL (Wide Flood)
AIMING	360 degrees horizontally, 180 degrees vertically
FINISH	AWH (Architectural White) ABK (Architectural Black) Custom RAL
DIMMING	Flicker Free 10% Dimming TRIAC forward-phase or leading-edge 120V.
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



OPTICS

A polycarbonate optical refractor allows for precise beam control and even distribution, with a variety of lumen options.

CONSTRUCTION

All track heads are designed using a proprietary coolLED Advanced Thermodynamic Design. The track head body is constructed of extruded aluminum, with a die-cast custom designed concealed heat sink, providing a thermal management system that is engineered for extremely long life and service period.

FINISH

Post-painted available in white, black and custom RAL colors.

ACCESSORIES

Track heads may accommodate 1 to 3 accessories. Please consult factory for standard or custom options.

TRACK COMPATIBILITY

Track heads are standard, with the compatibility for use with Mono-point, 1-Circuit, and 2-Circuit type H track. Please consult factory for 2-Circuit, 2-Neutral 120V Track.

DIMMING AND DRIVER INFORMATION

DIMTR – Electronic constant current LED driver compatible with TRIAC forward-phase or leading-edge dimming. Available in 120V. Dimmable down to 1%, standard. The LED driver is rated for 50 to 60Hz at 120V input, produces less than 20%THD, and has a power factor between 90% and 100%, and is thermally protected for additional safety.

WARRANTY

Five-year warranty for parts and components. (Labor not included)

Example: **ET-LED-329-600L-DIMTR-120-30K-90-FL-AWH**

SERIES	LUMENS	DIMMING	CCT/CRI	OPTICS	COLOR
ET-LED-329	 600L - 600 lumens	 DIMTR-120	 30K-90	 SP - Spot 15°  NFL - Narrow Flood 24°-25°  FL - Flood 36°-38°  WFL - Wide Flood 60°	 AWH - Architectural White  ABK - Architectural Black

ET-LED-329-600L-DIMTR-120-30K-90-FL-AWH

INPUT WATTS: **10.1**

LUMENS: **635**

CRI: **90**


EFFICACY: **63**

CCT: **3000K**

TEST NO.: **EL111810**

SPACING CRITERIA: **0.58**

Candle Power Distribution (Candelas)



Zonal Lumens Summary

Zone	Lumens	%Lamp	%Fixt
0-20	387.15	61.20	61.00
0-30	544.63	86.20	85.80
0-40	596.60	94.40	94.00
0-60	629.08	99.50	99.10
0-80	634.20	100.30	99.90
0-90	634.72	100.40	100.00

Luminance (Average candela/M²)

Angle in Degrees	Average 0°	Average 45°	Average 90°
45	5056	6655	16225
55	2540	3350	4301
65	762	1633	2613
75	322	838	1354
85	126	1433	2338

Lumens Per Zone

Zone	Lumens
0-10	131.74
10-20	255.42
20-30	157.47
30-40	51.98
40-50	23.20
50-60	9.27
60-70	3.94
70-80	1.18
80-90	0.52

Candela Tabulation

0	1530.71
5	1385.26
15	787.64
25	175.20
35	43.52
45	16.32
55	6.65
65	1.47
75	0.38
85	0.05
90	0.02

Coefficients of Utilization - Zonal Cavity Method Effective Floor Cavity Reflectance 0.20

	RC	80%				70%				50%				30%				10%				0%			
		70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	0%	0%	0%
ROOM CAVITY RATIO	0	120	120	120	120	117	117	117	117	112	112	112	107	107	107	102	102	102	102	102	102	100	95	95	95
	1	115	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	96	95	94	92	90	88	86
	2	110	106	102	99	108	104	101	98	101	98	96	98	96	94	95	93	92	90	88	85	83	81	79	77
	3	105	100	95	92	103	98	94	91	96	93	90	93	91	88	91	89	87	84	81	78	75	72	71	69
	4	101	95	90	86	99	93	89	86	91	88	85	89	86	84	88	85	83	80	77	74	71	68	66	65
	5	97	90	85	81	96	89	84	81	87	83	80	86	82	79	84	81	79	77	74	71	68	66	65	64
	6	93	86	81	77	92	85	80	77	83	79	76	82	78	76	81	78	75	74	72	70	68	66	65	64
	7	90	82	77	73	89	81	76	73	80	76	73	79	75	72	78	74	72	71	70	68	66	65	64	63
	8	86	78	73	70	85	78	73	70	77	72	69	76	72	69	75	71	69	68	67	66	65	64	63	62
	9	83	75	70	67	82	75	70	67	74	69	66	73	69	66	72	69	66	65	64	63	62	61	60	59
	10	80	72	67	64	79	72	67	64	71	67	64	70	66	64	70	66	63	62	61	60	59	58	57	56

RC - Ceiling Cavity Reflectance

RW - Wall Reflectance